

- Standard Features -

- Custom Options -



M Series

M6S-111SHC

2WD MIDSIZE UTILITY TRACTOR, ELECTRO-HYDRAULIC SHUTTLE TRANSMISSION & CAB

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

DIESEL ENGINE

Kubota V3800 Direct Injection  
 3.8L (230 cu. In.) 4 Cyl  
 EPA Tier 4 Final Compliant  
 Common Rail Electronic Fuel Injection  
 Electronic Engine Management  
 Turbocharged  
 12V 900 CCA Battery  
 Charging Output 80 amps Cab

TRANSMISSION

16F/16R or 32F/32R Swing Shift Plus  
 Shuttle Shift: Electric Hydraulic  
 Main Shift: 8-Speed synchronized  
 w/swing shift  
 Range Shift: 2-Speed Constant Mesh  
 Dual Speed: 2-Speed power shift  
 Clutch - Multi-Plate Wet  
 Planetary Final Drives  
 Hydraulic Wet Disc Brakes

MODEL SPECIFICATIONS

SAE Gross HP: 114  
 Engine Net HP: 105  
 Max. PTO HP: 95

FRONT AXLE

Hydrostatic Power Steering  
 2WD: Steel Adjustable  
 4WD: Cast Iron, Bevel Gear 55 Deg  
 Mechanical Differential Lock  
 Adj. (Rim) Tread Spacing

EXHAUST EMISSION CONTROL TYPE

DPF System (Diesel Particulate Filter)  
 SCR System  
 DEF Tank Capacity: 4.2 Gal

FLUID CAPACITY

Fuel Tank Capacity: 46.2 gal  
 Cooling System: 2.5 gal  
 Crankcase: 2.8 gal  
 Hydraulics/Trans: 15.8 gal  
 Front Axle case: 1.9 gal  
 Bevel Gear case: 0.9 gal

HYDRAULICS / HITCH / DRAWBAR

Open Center Gear Pump  
 Max. Flow @ Rated Engine Speed:  
 Cab: 2600 RPM  
 Power Steering: 12.9 gpm  
 Impl. Flow: 17.6 gpm  
 Total Flow: 30.5 gpm

INSTRUMENTS

LCD Display:  
 shuttle position, DEF gauge,  
 Clock, Travel Speed, PTO RPM,  
 Hour Meter, Trip Meter,  
 Fuel Consumption, PM Level, RPM  
 Memory  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature  
 Swing Shift H/L Digital Light Indicator  
 4WD Indicator  
 Water Separator Ligh

REMOTE VALVES

(1) SCD (Self Canceling Detent)  
 (1) FD (Float Detent)

3 POINT HITCH & DRAWBAR

Cat II 3-point Hitch  
 @ Lift Points: 4960 lbs  
 (ASAE) @ 24" Behind: 3858 lbs  
 Telescoping Lower Links  
 Stabilizers  
 Swinging Drawbar

CAB

Tilt Steering Wheel  
 Retractable Seat belt  
 12V - Outlet  
 Cup Holder  
 Cloth Suspension Seat  
 Side view mirrors  
 Front wiper and washer

POWER TAKE OFF

Live-Independent Hyd. PTO  
 SAE 1 3/8" Six Spline  
 540 rpm @ 2405 Eng. rpm  
 1000 RPM @ 2389 Eng. RPM  
 Optional 540/1000 standard on  
 2 speed PTO Model

SAFETY EQUIPMENT

Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 Turn Signals  
 SMV Sign  
 7-Pin Electrical Trailer Connector

LIGHTING

2 Headlights - Tail lights  
 4 Hazard Flasher Lights w/ Turn Signals  
 2 Grille Mounted Worklights  
 2 Cab Mounted Worklights  
 2 Rear Cab Mounted Worklights

SELECTED TIRES

AMR8980B & AMR9244D  
 FRONT - 10.00-16 F2 CHAMP GUIDE GRIP TL  
 REAR - 18.4-34 R1 8-PLY BIAS SAT II

M6S-111SHC Base Price: \$70,059.00

Configured Price: \$70,059.00

Sourcewell Discount: (\$15,412.98)

SUBTOTAL: \$54,646.02

Factory Assembly: \$260.00

Dealer Assembly: \$0.00

Freight Cost: \$737.50

PDI: \$250.00

Tire Tax: \$7.00

Dealer Training: \$250.00

Delivery: \$250.00

Sales Tax: \$4,652.47

Total Unit Price: \$61,052.99

Quantity Ordered: 1

Final Sales Price: \$61,052.99

**Purchase Order Must Reflect  
 the Final Sales Price**

To order, place your Purchase Order directly with the quoting dealer