



Jul 24, 2023

CITY OF MERCED
 Account # 0129519
 1776 GROGAN AVENUE
 MERCED, California 95340
 Attention: **WALLY BROUGHTON**

New Caterpillar Model: CB2.7 GC Paving and Compaction with all standard equipment in addition to the additional specifications listed below:

STOCK NUMBER: M24050 SERIAL NUMBER: 064100674 YEAR: 2023 SMU: 3

ADDITIONAL SPECIFICATIONS

Reference #	Description of Material and Equipment	Reference #	Description of Material and Equipment
547-4537	CB2.7 GC 03A UTILITY COMPACTOR	568-5154	LIGHTS, WORKING, LED
453-9461	TRAVEL CONTROL, CUP HOLDER	564-8160	ENGINE, CAT C1.7T
577-1414	PRODUCT LINK, CELLULAR PL243	574-6088	ROPS, FOLDABLE, LOCKABLE
574-6030	INSTRUCTIONS, ANSI	603-5887	DRUM SCRAPER, FOLDING
573-5962	SEAT, WITH SAFETY SWITCH	559-1655	HYDRAULICS, STD
364-2279	SUPPORT, SLIDING FOR SEAT	542-6995	SEAT BELT, 3"
569-8093	GUARDS, BUMPER	421-8926	SERIALIZED TECHNICAL MEDIA KIT
614-3613	MIRROR, REAR VIEW	0P-9002	LANE 2 ORDER
565-3708	SWITCH, BATTERY DISCONNECT	0G-0044	ROLL ON-ROLL OFF
574-6039	OIL, HYD, STANDARD		ENGINE S/N: J3301136
503-1603	PLUG (NON SINGLE LIFT)		

WARRANTY INFORMATION

Standard Warranty:

12 months / unlimited hours

Extended Warranty:

CB2.7GC-48 MO/4000 HR POWERTRAIN + HYDRAULICS + TECH

CSA

Dry Parts Kit - 24 MO/1000 HR, Dry Parts Kit - 24 MO/1000 HR

List Price	\$74,534.59
Sourcwell Government Discount	-\$16,040.84
Sales Tax (8.25%)	\$4,825.73
After Tax Balance	\$63,319.48

Sourcwell Contract #020223-CAT

STANDARD EQUIPMENT

POWERTRAIN -CAT C1.7T diesel engine --Turbocharged, EPA tier 4 final and EU -stage IV certified engine with DOC/DPF -aftertreatment --Gross power per ISO 14396 18.4 kW (24.7 -hp) @2200 RPM --Liquid cooled, direct injection -Aftercooler, air to air (ATAAC) -Fuel filter/water separator/electronic -priming pump and electronic water -indicator -Dual element air cleaner with dust -ejection -3 Engine speeds - idle, med, high -Engine belt guard -Programable auto Idle Shutdown -Aluminum bar plate cooling system -Hydrostatic transmission -Auto warmup cycle -Hydraulic on demand cooling fan -Service and parking brakes - spring -applied hydraulically released

ELECTRICAL -Engine start switch with auto preheat -12-volt starting and charging system -85-ampere alternator -Maintenance free battery, 750 CCA -Isolated and cooled battery -compartment -Backup alarm and front facing warning -horn -Product Link ready -Beacon ready -Diagnostic connector -CAT ET Compatible -Labeled and sealed electrical connectors -LED work lights (2 front, 2 rear)

OPERATOR ENVIRONMENT -Gauge Cluster: --Water level gauge --Fuel level gauge --Engine coolant temperature gauge --Hour meter --Faults -Simple rocker switches -Emergency stop switch -Operator warning system indicators: --Parking brake engaged --Operator out of seat --Hydraulic oil temperature high --Hydraulic oil restriction --Engine oil low pressure --Electrical system voltage low --Low fuel --Engine preheat --Engine emission system --High/low vibe frequency --Beacon status -Lockable, vandalism guard for -instrument panel -Travel control, single lever -High Vis Orange retractable seatbelt, -76mm (3") -2 platform handrails / single guardrail -Steering wheel spinner -12-volt power point -ROPS -Sealed storage compartment -Isolated operator platform -Vibration reducing, diesel resistant -rubber floormat -

DRUMS -Two smooth drums: 1200 mm (47") -wide x 720 mm (28") diameter and -14 mm (0.55") thick -Single amplitude with dual frequency -vibratory system -Automatic vibration control to prevent -vibration in neutral -Selection of front drum or both drum -vibration -Pressurized drum watering system with -selectable continuous or intermittent -flow -4 nozzle spray bars -Triple spray system filtration

FLUIDS -Premixed 50% concentration of extended -life coolant with freeze protection -to -37C (-35F) -

OTHER STANDARD EQUIPMENT -Lockable engine enclosure with safety -hold open latch -Lockable external fuel fill -Sealed for life hitch bearings -Sight gauges: --Hydraulic tank level --Engine Coolant -Lockable hydraulic tank cap -Articulated frame with safety lock -3 point hitch -4 transport tie-down and 4 lift points -63L (16.3 gal) fuel tank capacity -200L (52.8 gal) water tank capacity -6 Quick connect hydraulic pressure -test ports + 1 SOS port -Caterpillar o-ring face-seals couplings -Offset hitch with 50 mm (2") of -manual adjustment -Ecology drains: --Hydraulic Tank --Radiator --Engine Oil

This quote is good for (30) days. Any machine quoted outside of HOLT of CALIFORNIA's inventory is subject to revision All quotes are subject to credit approval and prior sale. Any quoted interest rates are subject to change without notice. Quote is void unless machine is delivered, and remains, within HOLT of CALIFORNIA's Dealership territory for two years or unless the machine has at least 1000 hours if delivered outside of Holt's territory.

THE ADDITIONAL TERMS AND CONDITIONS ON THE REVERSE SIDE ARE PART OF AND INCORPORATED IN THIS AGREEMENT. THIS AGREEMENT SHALL NOT BE CONSIDERED ENFORCEABLE UNTIL ACCEPTED BY HOLT AND EXECUTED BY ITS OFFICE. ANY INDIVIDUAL SIGNING THIS AGREEMENT REPRESENTS AND WARRANTS THAT HE/SHE IS AT LEAST 18 YEARS OLD AND HAS THE AUTHORITY TO BIND CUSTOMER TO THE TERMS OF THE AGREEMENT.

Accepted by

Date,

(Please Print)

Signature

Sincerely,
 Louie Soares
 Machine Sales Representative
 Holt of California
 Isoares@holtca.com
 209-401-4445