

Vehicles

CITY OF MERCED
PURCHASING DEPARTMENT
purchasing@cityofmerced.org

BID FORM

MAIL SEALED BIDS TO:
678 W 18th St Merced CA
95340

**PARCEL POST OR HAND
DELIVER BIDS TO:**
2525 "O" ST MERCED CA
95340

QUOTE HEREON YOUR LOWEST PRICE F.O.B. MERCED (INCLUDING BUT NOT LIMITED TO DISCOUNTS, REBATES, REGISTRATION AND OTHER FEES IN UNIT PRICE) FOR THE FOLLOWING EQUIPMENT, MATERIALS, SUPPLIES OR SERVICES. NO ALLOWANCE FOR FREIGHT, CARTAGE, PACKING, OR POSTAGE UNLESS SPECIFIED ON THIS BID. WHERE BRAND OR MAKE IS SPECIFIED, SIMILAR OR EQUAL WILL BE CONSIDERED.

SEALED BIDS DUE:

Tuesday, August 6th, 2024 at 2:00 P.M.

DEPT: Land Application

REQUISITION NO: 08062024

QTY	UOM	DESCRIPTION	PRICING
1	Each	Compact track loader (Specs 1-8)	UNIT PRICE \$ 65270.40
1	Each	Hopper sweeper (Spec 9)	UNIT PRICE 6174.24
			DELIVERY COST 2810.33
			SALES TAX (8.25%) 6126.04
			CA TIRE FEE 5
			EXTENDED WARRANTY 0
			TOTAL AMOUNT \$80,381.01

Notice: Submit one original bid and one copy
see Attached Sourcewell B.O

* BID OPENING WILL BE HELD IN THE PURCHASING OFFICE CONFERENCE ROOM AT 2525 "O" STREET, MERCED, CA *

We have stated hereon the prices at which we will furnish and deliver the equipment, materials, supplies or services as specified above.

Delivery will be made in 120 days after receipt of order (A.R.O.), except as otherwise indicated.

Note: The City reserves the right to reject any and or all bids, split the bid award, or to accept the bid that best serves the public purpose, even though it may not be the lowest.

COMPANY: GARTON TRACTOR Inc.

BY: Kim Bishop

TITLE: Sales

SIGNATURE: Kim Bishop

DATE: 8/2/2024

PHONE: 209-620-7706

EMAIL: kbishop@gartontractor.com

PAYMENT TERMS: (Net 10, 30, 45)

NOTICE:
ALL BIDS MUST BE SIGNED

Quote Provided By
GARTON TRACTOR, INC.

Kim Bishop

700 S. Hwy 59

Merced, CA 95341

email: kbishop@gartontractor.com

phone: 2096207706

- Standard Features -

- Custom Options -

**Kubota**

S Series

SVL75-3HFWC

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Vertical Lift Path Loader Frame
Standard Front Quick Coupler,
Float Standard
Hydraulic Quick Coupler Option
Selector Loader Arm Self-
Leveling
Loader Boom Lock
Open ROPS & Air Conditioned
ROPS/FOPS Cab Models
High Back, Adjustable, Vinyl,
Suspension Seat
2" Retractable Seat Belt and 2-
Piece Seat Bar
12V Electric Outlet
19.2 gpm Auxiliary Hydraulics
standard, 29.8 gpm Option
Direct To Tank Return Line
Rigid Mounted Undercarriage, 4
Lower Track Rollers
Rubber Tracks, 12.6" Standard,
15" Optional
Two Speed Travel System
Automatic Wet Disk Parking
Brake
Kubota 4 Hydraulic Pump Load
Sensing System
2 Gear, 2 Variable
Displacement Pumps
Hydraulic Joystick Controls,
Optional Multi-Functional Grips
ISO Operating Pattern
Hand And Foot Throttle
Controls
Electronic Travel Torque
Management
Automatic Glow Plugs
7" Multifunction Touch Screen
Integrated Rear Camera
Keyless Start
Self Bleed Fuel System
2 Front and 2 Rear Working
Lights
Hour Meter, Engine
Temperature and Fuel
Gauges and Warning Lights
Horn and Backup Alarm
Lockable Fuel Cap
Bolt On Grab Handles to enter
machine
KubotaNOW Telematics

BASIC UNITS

SVL75-3, 15.8" Rubber Tracks,
Open ROPS/FOPS Cab
Hydraulic Quick Coupler
High Flow Hydraulics & MF Grips
14-Pin Coupler

ENGINE
V3307 Kubota CR-TE4, Tier 4
Diesel Engine
4 Cylinder, 4 Cycle, Turbo Charged
74.3 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 81.8"
Width (without attachment) 65.9"
Width with wide track option
(without attachment) 69.1"
Length (without attachment) 112.0"
Length of Track on Ground 56.5"

OPERATIONAL**DIMENSIONS**

Operating Weight*, SVL75H, 12.6"
Rubber Tracks, Open
ROPS/FOPS Cab, Mechanical
Quick Coupler 9,190 lbs.
Rated Operating Capacity (@ 35%
of Tipping Load) 2,490 lbs.
Rated Operating Capacity (ROC)
@ 35% of Tipping Load complies
with ISO 14397-1 and SAE J 818
for crawler loaders
Rated Operating Capacity (ROC)
@ 50% of Tipping Load 3,557 lbs.
Tipping Load 7,112 lbs.
Auxiliary Hydraulics Flow 192/
29.8 gpm
Travel Speed (Low / High)
5.6 / 8.6 mph
Reach @ Maximum Height 39.6"
Height to Hinge Pin 122.7"
Ground Pressure (Standard Track)
5.8 psi
Ground Pressure (Wide Track) 4.7
psi
Traction Force 9,678 lbf.

* Includes operator's weight, 175
lbs.

SVL75-3HFWC Base Price: \$82,019.00

(1) AT&T TELEMATICS MODEM \$449.00
DCU6700-AT&T TELEMATICS MODEM

(1) 74" Heavy Duty, Low Profile, Long Floor, Cutting
Edge, Side Cutter, 19.2 cu-ft heaped capacity \$2,604.00
AP-HD74LLC-74" Heavy Duty, Low Profile, Long Floor, Cutting
Edge, Side Cutter, 19.2 cu-ft heaped capacity

(1) AIR RIDE SEAT SUSPENSION KIT \$690.00
S6679-AIR RIDE SEAT SUSPENSION KIT

(1) 3" RETRACTABLE SEAT BELT KIT \$94.00
K9926-3" RETRACTABLE SEAT BELT KIT

(1) HOSE STAY FOR SSV/SVL MODELS \$108.00
S6763-HOSE STAY FOR SSV/SVL MODELS

(1) REAR VIEW MIRROR KIT \$25.00
S6641-REAR VIEW MIRROR KIT

(1) HB Series Hopper Broom, 74" Width \$8,124.00
AP-HB74-14-HB Series Hopper Broom, 74" Width

Configured Price: \$94,113.00

Sourcewell Discount: (\$22,668.36)

SUBTOTAL: \$71,444.64

Dealer Assembly: \$287.83

Freight Cost: \$887.50

PDI: \$400.00

safety training \$485.00

Dealer Delivery and attachment setup \$750.00

Sales tax @ 8.25% \$6,126.04

Total Unit Price: \$80,381.01

Quantity Ordered: 1

Final Sales Price: \$80,381.01

Purchase Order Must Reflect Final Sales Price.To order, place your Purchase Order directly with the quoting
dealer

*Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.

Vehicles

* Projected Resale Value based on www.BlackBookPricePoint.com 72-month residual.

** Maintenance, Repair, and Fuel Costs based on www.Edmunds.com

C. Specifications

Bid specifications for Compact Track Loader

1. Engine horsepower minimum requirement of 74 HP.
2. Unit to be furnished with enclosed cab with climate control AC, heater, and radio.
3. Unit to be equipped with joystick controls for maneuvering and bucket operation.
4. Unit to be equipped with auxiliary hydraulic connections for accessories and appropriate hydraulic capacity to operate attachments.
5. Unit to be equipped with hydraulic quick connectors for in cab attachment of buckets and accessories.
6. Unit to have a minimum operating weight of 9100 pounds.
7. Unit to come with standard duty bucket with a minimum bucket width of 68 inches.
8. Unit to come equipped with 15-inch tracks with standard duty tread suitable for all terrain types.
9. Unit to come equipped with additional 74" hopper sweeper with poly bristles without gutter attachments or dust control. Angle brooms or units without collection hoppers are non-qualified.