

-- Standard Features --

-- Custom Options --



Kubota

S Series

SSV75HFRC

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

## FEATURES

Vertical Lift Path Loader Frame  
 Standard Front Quick Coupler,  
 Float Standard  
 Hydraulic Quick Coupler Option  
 One Way Self-Leveling  
 with Kubota Shock-less Ride  
 (KSR) Option  
 Loader Boom Lock  
 Open ROPS & Air Conditioned  
 ROPS/FOPS Cab Models  
 Adjustable, Vinyl, Suspension  
 Seat  
 2" Retractable Seat Belt and 2-  
 Piece Seat Bar  
 12V Electric Outlet  
 20.9 gpm Auxiliary Hydraulics,  
 30.4 gpm High Flow Hydraulics  
 Option  
 Direct To Tank Return Line  
 12x16.5, 10PR Heavy-Duty  
 Tires  
 Two Speed Travel System  
 Spring Applied Hydraulically  
 Released (SAHR) Brakes  
 Gear Drive Pumps & Variable  
 Loader  
 and High Flow Pumps (if  
 equipped)  
 Mechanical Hand & Foot  
 Controls  
 Electronic Dial Throttle  
 Automatic Glow Plugs  
 Key Switch Stop/Start System  
 Self-Bleed Fuel System  
 2 Front and 2 Rear Working  
 Lights  
 2 Front Corner Lights & 2 Rear  
 Red Tail Lights  
 Hour Meter, Engine  
 Temperature and Fuel  
 Gauges and Warning Lights  
 Horn and Backup Alarm  
 Lockable Fuel Cap Door  
 Bolt On Grab Handles to enter  
 machine

## BASIC UNITS

SSV75HFRC, AC Enclosed Cab,  
 High Flow Hydraulics,  
 Self-Leveling with KSR,  
 Hydraulic Quick Coupler

## OPERATIONAL

## DIMENSIONS

Operating Weight\*, SSV75\*,  
 Open ROPS/FOPS Cab,  
 Mechanical Quick Coupler 8,157  
 lbs.  
 Rated Operating Capacity (ROC)  
 @ 50% of Tipping Load 2,690 lbs.  
 Tipping Load 5,380 lbs.  
 Auxiliary Hydraulics Flow 20.9 /  
 30.4 gpm  
 Travel Speed (Low / High) 7.1 /  
 11.8 mph  
 Reach @ Maximum Height 36.9"  
 Height to Hinge Pin 128.3"  
 Ground Clearance 8.1"  
 Traction Force 8,494 lbf.

\* Includes operator's weight, 175  
 lbs.

## ENGINE

V3307 Kubota CR-TE4, Tier 4  
 Diesel Engine  
 4-Cylinder, 4 Cycle, Turbo Charged  
 71.6 Gross HP @ 2600 rpm  
 3.3 L Displacement  
 196 lbf-ft Peak Torque

## DIMENSIONS

Cab Height 81.3"  
 Width over wheels 71.8"  
 Width with 68" standard bucket  
 75.0"  
 Length without bucket 115.0"  
 Length with standard bucket  
 144.1"

SSV75HFRC Base Price: \$65,425.00

(1) 74" Heavy Duty Low Profile, Long Floor, Teeth,  
 Side Cutter, 19.2 cu-ft heaped capacity  
 AP-HD74LLT-74" Heavy Duty Low Profile, Long Floor, Teeth,  
 Side Cutter, 19.2 cu-ft heaped capacity

(1) RETRACTABLE SEAT BELT OPTION (3" WIDE) \$97.00  
 K9926-RETRACTABLE SEAT BELT OPTION (3" WIDE)

(1) HOSE STAY FOR SSV/SVL MODELS \$112.00  
 S6763-HOSE STAY FOR SSV/SVL MODELS

(1) 20 Series Post Hole Digger \$4,335.00  
 SA20 -05-42-51-12-20 Series Post Hole Digger

(1) TR Series Trencher, 48" Width \$13,174.00  
 AP-TR48-11-38-61-70-TR Series Trencher, 48" Width

Configured Price: \$85,734.00

Sourcewell Discount: (\$20,751.25)

SUBTOTAL: \$64,982.75

Dealer Assembly: \$45.83

Freight Cost: \$831.25

PDI: \$400.00

Training: \$250.00

Tire Tax: \$7.00

Sales Tax: \$5,487.06

Total Unit Price: \$72,003.89

Quantity Ordered: 1

Final Sales Price: \$72,003.89

**Purchase Order Must Reflect Final Sales Price.**

To order, place your Purchase Order directly with the quoting  
 dealer

\*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.