

-- Standard Features --

-- Custom Options --



S Series SSV75HFRC

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Vertical Lift Path Loader Frame
 Standard Front Quick Coupler,
 Float Standard
 Hydraulic Quick Coupler Option
 One Way Self-Leveling
 with Kubota Shock-less Ride
 (KSR) Option
 Loader Boom Lock
 Open ROPS & Air Conditioned
 ROPS/FOPS Cab Models
 Adjustable, Vinyl, Suspension
 Seat
 2" Retractable Seat Belt and 2-
 Piece Seat Bar
 12V Electric Outlet
 20.9 gpm Auxiliary Hydraulics,
 30.4 gpm High Flow Hydraulics
 Option
 Direct To Tank Return Line
 12x16.5, 10PR Heavy-Duty
 Tires
 Two Speed Travel System
 Spring Applied Hydraulically
 Released (SAHR) Brakes
 Gear Drive Pumps & Variable
 Loader
 and High Flow Pumps (if
 equipped)
 Mechanical Hand & Foot
 Controls
 Electronic Dial Throttle
 Automatic Glow Plugs
 Key Switch Stop/Start System
 Self-Bleed Fuel System
 2 Front and 2 Rear Working
 Lights
 2 Front Corner Lights & 2 Rear
 Red Tail Lights
 Hour Meter, Engine
 Temperature and Fuel
 Gauges and Warning Lights
 Horn and Backup Alarm
 Lockable Fuel Cap Door
 Bolt On Grab Handles to enter
 machine

BASIC UNITS

SSV75HFRC, AC Enclosed Cab,
 High Flow Hydraulics,
 Self-Leveling with KSR,
 Hydraulic Quick Coupler

OPERATIONAL

DIMENSIONS

Operating Weight*, SSV75*,
 Open ROPS/FOPS Cab,
 Mechanical Quick Coupler 8,157
 lbs.
 Rated Operating Capacity (ROC)
 @ 50% of Tipping Load 2,690 lbs.
 Tipping Load 5,380 lbs.
 Auxiliary Hydraulics Flow 20.9 /
 30.4 gpm
 Travel Speed (Low / High) 7.1 /
 11.8 mph
 Reach @ Maximum Height 36.9"
 Height to Hinge Pin 128.3"
 Ground Clearance 8.1"
 Traction Force 8,494 lbf.

* Includes operator's weight, 175
 lbs.

ENGINE

V3307 Kubota CR-TE4, Tier 4
 Diesel Engine
 4-Cylinder, 4 Cycle, Turbo Charged
 71.6 Gross HP @ 2600 rpm
 3.3 L Displacement
 196 lbf-ft Peak Torque

DIMENSIONS

Cab Height 81.3"
 Width over wheels 71.8"
 Width with 68" standard bucket
 75.0"
 Length without bucket 115.0"
 Length with standard bucket
 144.1"

SSV75HFRC Base Price: \$65,425.00

(1) 74" Heavy Duty Low Profile, Long Floor, Teeth,
 Side Cutter, 19.2 cu-ft heaped capacity
 AP-HD74LLT-74" Heavy Duty Low Profile, Long Floor, Teeth,
 Side Cutter, 19.2 cu-ft heaped capacity

(1) RETRACTABLE SEAT BELT OPTION (3" WIDE) \$97.00
 K9926-RETRACTABLE SEAT BELT OPTION (3" WIDE)

(1) HOSE STAY FOR SSV/SVL MODELS \$112.00
 S6763-HOSE STAY FOR SSV/SVL MODELS

(1) 20 Series Post Hole Digger \$4,335.00
 SA20 -05-42-51-12-20 Series Post Hole Digger

(1) TR Series Trencher, 48" Width \$13,174.00
 AP-TR48-11-38-61-70-TR Series Trencher, 48" Width

Configured Price: \$85,734.00

Sourcewell Discount: (\$20,751.25)

SUBTOTAL: \$64,982.75

Dealer Assembly: \$45.83

Freight Cost: \$831.25

PDI: \$400.00

Training \$250.00

Tire Tax \$7.00

Sales Tax \$5,487.06

Total Unit Price: \$72,003.89

Quantity Ordered: 1

Final Sales Price: \$72,003.89

Purchase Order Must Reflect Final Sales Price.

**To order, place your Purchase Order directly with the quoting
 dealer**

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.